



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE AB-030SHS

DESCRIPTION: Woven Satin Acetate, Heat Seal Coated

SPECIFICATIONS:

Total Weight: 9.75 ± 0.40 oz./sq. yd.
Fabric: 2.65 ± 0.20 oz./sq. yd.
Adhesive: 7.10 ± 0.20 oz./sq. yd.

Total Thickness: 0.0117 ± 0.001 in.
Fabric: 0.0056 ± 0.001 in.
Adhesive: 0.0061 ± 0.001 in.

Opacity: > 95%
Sealing Temperature: 180°-240°F
Gurley Stiffness (MD): 511 ± 100 mg
Gurley Stiffness (CD): 311 ± 50 mg

GENERAL: AB-030SHS is a woven satin acetate, suitable for offset printing. The back side of the product is coated with a heat seal adhesive that is designed to bond to rough, porous surfaces. The recommended sealing conditions for the adhesive is a temperature 200°F, dwell time of 4 seconds, and a platen pressure of 10 PSI. The adhesive can also be applied using standard heat tunnel equipment as used for carpet sample labeling. AB-030SHS should not be applied to olefin or non-stick materials.

AB-030SHS has a standard shelf life of one year and should be kept in a clean, dry place between 40°-100°F.

**Recommended
Printing Methods:** Offset, Dot Matrix

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com