PRODUCT SPECIFICATIONS



STYLE AM-337P

DESCRIPTION: Woven Acetate, Pearlescent

SPECIFICATIONS:

Total Weight: 3.40 ± 0.5 oz./sq. yd. Thickness: 0.0067 ± 0.0010 in.

Opacity: 91%

Gurley Stiffness (MD): 40 ± 10 mg
Gurley Stiffness (CD): 20 ± 10 mg
Tear Strength (MD): 100 ± 20 grams
Tear Strength (CD): 120 ± 50 grams

GENERAL: Coated with urethane on both sides and coated with a satin finish on

one side. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Ravel proof edges. Exhibits

excellent punching capabilities.

Recommended

Printing Methods: Flexography, Screen Printing, Offset, Hot Stamping and Dot Matrix

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group Worthen Industries 1125 41st Street SE Grand Rapids, MI 49508

Tel: (616) 742-8990 Fax: (616) 742-8995 www.worthenindustries.com