



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE RP-133Y

DESCRIPTION: Yellow Nonwoven Spun-bonded Polyester

SPECIFICATIONS:

Total Weight: 4.40 ± 0.40 oz./sq. yd.
Total Thickness: 0.0070 ± 0.0010 in.
Opacity: 98%
Burst Strength: 66 lbs.
Stiffness (MD): 74 ± 20 mg
Stiffness (CD): 67 ± 20 mg
Tear Strength (MD): 300 grams (min)
Tear Strength (CD): 250 grams (min)
Tensile Strength (MD): 100 ± 25 lbs.
Tensile Strength (CD): 75 ± 20 lbs.

GENERAL: Coated with acrylic on both sides. Suited for conversion into permanent care labels. Meets DDD-L-20F, as well as AATCC IVA wash test requirements. Exhibits excellent punching capabilities, excellent smoothness of hand, with good resistance to fadeout of imprinting from repeated commercial washings and dry cleaning. The product is non-fraying, resistant to shrinking and curling, and effectively resistant to degradation from rot, mildew and perspiration. Both surfaces are receptive to printing by most commonly used methods without shadow strikethrough.

Recommended Printing Methods: Flexography., Screen Printing, Offset, Hot Stamp and Dot Matrix

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com