



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE TB-607W

DESCRIPTION: Fire Retardant Tyvek®, Thermal Transfer Printable

SPECIFICATIONS:

Total Weight: 1.80 ± 0.20 oz./sq. yd.
Thickness: 0.0062 ± 0.0010 in.
Opacity: 95%
Tear Strength (MD): 250 grams (min)
Tear Strength (CD): 430 grams (min)

GENERAL: TB-607W is a coated Tyvek® 4173DR Brillon grade, used mainly for information labels that require fire retardant properties. The uncoated side is calendared smooth for improved thermal transfer printing when using wax or wax/resin ink ribbons. This product meets requirements of FMVSS 302 and Federal Air Regulation 25.853, Compartment Interiors, Appendix F, Part 1, a, ii. This product is tested for compliance and Individual lot certifications will be sent at time of shipment.

**Recommended
Printing Methods:** Thermal Transfer, Flexo

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
1125 41st Street SE
Grand Rapids, MI 49508

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com